

AHD- 1.0MP (20mtr)

| | |
|-----------------------|---|
| Model | ESSS- |
| Image Sensor | 1/3" Sony CMOS / 2M Pixel |
| DSP+CCD | Nextchip 2441H+T001614 |
| Effective Pixels | PAL/NTSC: 1920*1080 |
| Scanning System | NTSC: 525 lines, 60 fields/sec |
| | PAL: 625 lines, 50 fields/sec |
| Sync System | Internal |
| MIN Illumination | 0.03 Lux / F1.2(0Lux / IR ON) |
| S/N Ratio | 52dB (AGC OFF) |
| Gamma Correction | 0.45 |
| Electronic Shutter | NTSC: 1/30~1/50,000 sec |
| | PAL: 1/25~1/50,000 sec |
| OSD | Support |
| White Balance | AWB/ATW/AWC/INDOOR/OUTDOOR/MANUAL |
| Gain Control | 0-15 |
| BLC | BLC/HSBLC/OFF |
| DNR | 2DNR, 3DNR |
| DWDR | ON/OFF/AUTO |
| Day/Night | Auto/B&W/Color/EXT |
| Mirror | ROTATE/OFF/MIRROR/V-FLIP |
| NEG. IMAGE | ON/OFF |
| CAM TITLE | ON/OFF |
| DEFECT | ON/OFF |
| Motion Detection | ON/OFF(4 Programmable Zone) |
| OSD Language | ENG,GER,FRA,ITA,SPA,POL,RUS,POR,NED,TUR,CH1,CH2 |
| IR LED | 36pcs φ5 IR LED |
| Video Output | AHD |
| Distance | 20mtr |
| IR Distance | 25mtr |
| Lens | 3.6mm Lens |
| Operation Temperature | -20 °C ~ 50°C |
| Operational Humidity | Within 95%RH |
| Material | Plastic / Metal |