

DVR 4 Channel



Processor	Dual-core embedded processor
O/S	Embedded LINUX
IP Camera Input	4 Channel(ANALOG, AHD, IP)
User Interface	GUI
Video Output	1 HDMI, 1 VGA
Compression	H.264
Video Resolution	1440*900, 1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768
Video Recording	Max 80 Mbps
Video Display Split	1/4/8/9/16
Motion Detection	MD Zones: 396(22x18).
Video Loss	Supports
Camera Blank	Supports
Hard Disk	1 SATA ports, up to 4TB
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
Recording Mode	Schedule(Regular(Continuous), MD, Alarm), Stop
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Model	USB Device / Internal SATA burner/ Network
Interface Ports	1 HDMI, 1 VGA, 2 USB2.0, 1 RJ45
Max User Account	16 Users
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Smartphone	iPhone, iPad, Android.
Protocols	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.3
Ethernet	RJ-45 port (10/100M/1000M)
Power Supply	DC12V/2A
Power Consumption	10W(without HDD)
Working Temp	-10 ~+55°C / 10~90%RH / 86~106kpa
cloud server	P2P